



## Expanded Polystyrene Manufacturers

ISOPOL LTD, P.O.BOX 54115, 3721 Limassol – Cyprus

Tel.: +357-25-724944, Fax: +357-25-729629, E-mail: isopol@cytanet.com.cy, VAT: CY-10008489 A, A.Φ.T.: 12008489C

### DECLARATION OF PERFORMANCE

No.02-305/11/EE October /2018

1. Unique identification code of the product-type:

**ISOPOL EPS 80 WHITE**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

**EPS-EN13163-CS(10)80-BS125-L2-W1-T1-S1-P3-WL(P)2,0-WL(V)2,5-DS(70,90)1-DS(N)2-MU20-TR180-SS86-GM1250**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Expanded polystyrene, intended to be used as thermal insulation in buildings.**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**ISOPOL LTD  
Ayios Athanasios Industrial Area,  
P.O.BOX 54115,  
3721 LIMASSOL-Cyprus**

Web site: <http://www.isopol.com.cy> – Email: [isopol@cytanet.com.cy](mailto:isopol@cytanet.com.cy)

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 3**

6. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **EN 13163:2012+A1:2015**

**IMBiGS N.B. 1454 -10/2018**

performed the initial testing of the product according to system 3 and issued test reports:

TEST REPORTS No. 45/18/99/M-1, No. 45/18/OWU/M1



## Expanded Polystyrene Manufacturers

ISOPOL LTD, P.O.BOX 54115, 3721 Limassol – Cyprus

Tel.: +357-25-724944, Fax: +357-25-729629, E-mail: isopol@cytanet.com.cy, VAT: CY-10008489 A, A.Φ.T.: 12008489C

### 7. Declared performance

Essential characteristics	Performance	Harmonized technical specification
<b>Reaction to fire</b>	<b>Euroclass E</b>	<b>EN 13163:2012 +A1:2015</b>
<b>Release of dangerous substances</b>	-	
Thermal resistance -Thermal conductivity, $\lambda_D$	<b><math>\lambda</math> DECLARED = 0,036 W/mK</b>	
-Thickness	<b>T1</b>	
-Thermal resistance, R ( $m^2$ K/W)	<b>Plate thickness / Thermal resistance</b> <b>50 mm / 1,39 - 60 mm / 1,66</b> <b>80 mm / 2,22 - 100 mm / 2,78</b> <b>120 mm / 3,33 - 150m / 4,17</b>	
Compressive strength -Compressive stress at 10 % deformation kpa	<b>CS(10)80</b>	
-Bending Strength kpa	<b>≥BS 160</b>	
-Tensile Strength kpa	<b>≥180</b>	
-Shear behaviour, $\tau$ , kpa	<b>86</b>	
-Shear Modulus, G, kPa	<b>1250</b>	
-Water vapour diffusion resistance Factor $\mu$	<b>30-70</b>	
-Water vapour permeability $\delta$ mg/(Pa.h.m)	<b>0,015 to 0.030</b>	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:  
Limassol, 30/04/2020

Loizou Demetris, director